











* level specified with ventilation system connected on the suction side and discharge side (may change depending on the state of clogging of the filter cartridges)

103864-150C / 150P FPMXL-10-150

Filter unit: stationary modular filtration unit designed for extraction and purification of air from dry dust - especially in welding. Version: C - CORE, P - PRO

Construction:

- damping compartment with radial fan
- ten filtering cartridges
- filter-regulator with pressure gauge
- welded steel construction, powder coated
- inlet module with metal prefilter
- five drawers for contaminants

Version CORE
- fan control VFD
- automatic filter cartridge cleaning system (timer)

Version PRO
- fan control VFD
- automatic filter cartridge cleaning system (timer/ ΔP)
- modbus TCP/IP for communication in industrial automation
- airflow rate control
- compressed air pressure control

Parameters:


• maximum airflow:	12000 m³/h
• sound pressure level at 1 m:	80 dB(A)*
• motor power:	15,0 kW
• number of phases / voltage:	3x400 V
• frequency:	50 Hz
• maximum motor speed:	2950 rpm
• total drawer capacity:	100 dm³
• maximum working temperature:	40 ºC
• weight:	1130 kg

Filters:
1. Metal prefilter - 1 pc.
2. Cartridge filter - 10 pcs.

Notes:

Required compressed air supply: 6.0 ± 0.2 bar

The method of packing and carton sizes:

2x 

A =	3200;	1800
B =	1200;	1200
H =	2000;	1200
Weight =	770 kg;	380 kg

All dimensions are in mm

Menegon Sp. z o.o.
Mokry Dwór 6C, 83-021 Mokry Dwór, PL
tel: +48 58 301 28 38 info@menegon.com.pl
www.menegon.com.pl

All rights reserved. This document inlcuding constructional and technical information as well as trademarks and brand names are law protected and are property of Menegon Sp. z o.o. The producer reserves the right to introduce changes in construction without prior notifictation.