



105758-022C / 022P FPMXL-02A-022

Filter unit: stationary modular filtration unit designed for extraction and purification of air from dry dust - especially in welding. Version: C - CORE, P - PRO

Construction:

- damping compartment with radial fan
- two filtering cartridges
- filter-regulator with pressure gauge
- welded steel construction, powder coated
- inlet module with metal prefilter
- one drawer for contaminants

Version CORE

- fan control on/ off
- automatic filter cartridge cleaning system (timer)

Version PRO

- fan control VFD
- automatic filter cartridge cleaning system (timer/ ΔP)
- modbus TCP/IP for communication in industrial automation
- airflow rate control
- compressed air pressure control

Parameters:

- maximum airflow: 2000 m³/h
- sound pressure level at 1 m: 76 dB(A)*
- motor power: 2,2 kW
- number of phases / voltage: 3x400 V
- frequency: 50 Hz
- maximum motor speed: 2950 rpm
- total drawer capacity: 20 dm³
- maximum working temperature: 40 °C
- weight: 340 kg

Filters:

1. Metal prefilter - 1 pc.
2. Cartridge filter - 2 pcs.

Notes:

Required compressed air supply: 6.0 ± 0.2 bar




The method of packing and carton sizes:

1x		A =	800
		B =	1200
		H =	2600
		Weight =	360 kg

All dimensions are in mm

Menegon Sp. z o.o.
Mokry Dwór 6C, 83-021 Mokry Dwór, PL
tel: +48 58 301 28 38 info@menegon.com.pl
www.menegon.com.pl

All rights reserved. This document including constructional and technical information as well as trademarks and brand names are law protected and are property of Menegon Sp. z o.o. The producer reserves the right to introduce changes in construction without prior notification.



* level specified with ventilation system connected on the suction side and discharge side (may change depending on the state of clogging of the filter cartridges)